



Clinex Dispersion Hard

Protective polymer coating

- Safe product for the user and the environment (no classification)
- Designed for high traffic areas Provides a
- long-lasting shine
- Has anti-slip properties
- Abrasion resistant
- Gives a satin sheen

Available
Packaging:

Index	Article name
77-671	Clinex Dispersion HARD 1L
77-672	Clinex Dispersion HARD 5L



Properties:

Preparation for floors based on acrylic and polyurethane polymers with shine properties. Creates a durable coating that is resistant to damage. Urethane reinforced coating protects the floors against dirt ingress and scratches. Preparation can be used on all types of tops: vinyl, tiles, terrazzo, concrete, PVC and others. It works well in places of heavy traffic. It has anti-slip properties. Successive polishing of surfaces covered with the product with high-rotary machines, increases the gloss effect, removes scratches and traces created during operation and prolongs the durability of the applied coating. The percentage of solids is about 25%. Properly applied coating is resistant to alcohol-based disinfectants. The product meets the ASTM D-2047-04 standards in terms of the coefficient of constant friction.

Directions for use:

1. Shake well before use
2. Remove all types of contaminants from the surface. Remove old polymer layers with Clinex Dispersion STRIPPER
3. On a clean, defatted, neutralized and well-dried surface, evenly apply the preparation with a mop. After even application of the first layer of the preparation, wait about 40 minutes. until the applied layer is completely dry
4. Depending on the desired final effect, it is recommended to apply 2-3 layers of the agent. Apply each subsequent layer of polymer only after the previous layer has completely dried (minimum drying time: 40 min.)
5. After application, the surface should be allowed to dry for at least 1.5 hours



Information & applications

INFO	APPLICATIONS							Application conditions	Avoid drafts, turn off fans
	ph	Concrete stone	Terrazzo	Linoleum	Pvc	Acrylic polymer	Acrylic polymer and polyurethane	Content solid substance	
HARD	9	✓	✓	✓	✓		✓	~25%	
									Substrate temperature
									10-30°C
									Room humidity
									60% Relative humidity
									Precautions
									up to 24h after application, protect the floor against heavy traffic
									Use
									Do not use strongly alkaline washing agents that can destroy the resulting coating

NOTE:

- For professional use only
- Before using the product, in a hardly visible place, check operation of the product on a small area.
- Do not use the preparation on surfaces not resistant to water
- Do not use strongly alkaline cleansers that may destroy the polymer layer

The Seller shall not be liable for any use of the product against its intended purpose.

SAFETY:

- Do not mix with other products.
- See the safety data sheet for additional product information.

STORAGE CONDITIONS:

- Store the product at 5 to 30°C.
- Store in original, sealed packaging only.